

De-Alconox B



**Thermal
Dealcoholisation
of beer**

- Processing at lowest temperatures (<39°C)
- Dealcoholisation down to <0.02% vol.
- Suitable for filtered and non-filtered beer



Application

Bucher Unipektin dealcoholisation plants are designed in a way to produce a highly dealcoholised beer as well as rectified alcohol with minimum negative side effects on beer quality. Additionally, the design is flexible regarding product flow and composition and is also well suitable for non-filtered beer. It is therefore a sustainable investment enabling a brewery to serve all current or future market trends.

Process

Firstly, the beer is gently degassed in order to avoid foaming throughout the process. The temperature of the incoming product is adjusted in counterflow to the outgoing dealcoholised beer. In a special Bucher Unipektin degassing system very low final gas levels are achieved at a pressure slightly below the boiling pressure. The alcohol is then removed from the beer and rectified in a special column. The column consists of two sections: a first section for stripping the alcohol out of the beer and a second section for rectifying the alcohol to the desired concentration.

The unique design of the used high precision inserts provides several advantages:

- minimum pressure drop allows a low temperature at the bottom of the column with least impact on beer quality and optimised energy consumption compared to similar systems
- high tolerance for suspended particles enabling troublefree processing of non-filtered beers
- very low alcohol content achievable providing maximum options for final blending with non-treated beer

The energy for the stripping and rectifying column is supplied by a small amount of vapour which is evaporated out of the already dealcoholised beer. Bucher Unipektin uses evaporator bodies with a large heat transfer surface which minimises the required surface temperature in contact with the product. Finally the beer is cooled back and carbonised again. The whole process is operated under vacuum limiting the product temperature to 39°C and excellently preserving the quality of the treated beers.

Technical data Capacities standardised dealcoholisation plants are available from 5 up to 200 hl/h.

Bucher Unipektin AG
Murzlenstrasse 80
CH-8166 Niederweningen
Tel. +41 44 857 23 00
info@bucherunipektin.com
bucherunipektin.com

Helpdesk
Tel. +41 44 857 22 22
service@bucherunipektin.com

Technical support
Tel. +41 44 857 22 33
support@bucherunipektin.com

Products and Services

Process technology for fruit and vegetable processing to juices, concentrates and puree production, for brewing solutions, for filtration, for milk powder production, for the vacuum drying of liquid and solid products, for freeze drying of coffee, tea, fruits, vegetable, etc. Technology for municipal and industrial sludge dewatering and drinking water filtration

Products

Fruit reception lines, mills, mash heaters, hydraulic presses, membrane filtration equipment, cold block equipment, adsorber, ion exchanger, evaporators and aroma plants, pasteurizers, CIP systems, vacuum and freeze drying cabinets and belt dryer, zeolite adsorber, complete processing lines

Services

Process development and project engineering; assembly and commissioning; technical support; original spare parts; inspection; service contracts; retrofits; training; service and maintenance; NetService